

ADVERTISED BID  
**CITY OF ST. LOUIS**

OFFICE OF THE SUPPLY COMMISSIONER  
 1200 MARKET ST RM 324  
 ST LOUIS MO 63103-2842



REQUEST FOR QUOTE  
 42012Q0344

PAGE  
 1

ADDRESS CORRESPONDENCE TO

... We agree to furnish the following articles to the City of St. Louis,  
 free of any extra charges, in the quantity named and at the prices respectively  
 stated:

T  
O

S  
H  
I  
P  
T  
O

LAMBERT AIRPORT  
 CENTRAL STORES  
 4780 ST ANDREW LANE  
 BRIDGETON MO 63044

SEE TERMS AND CONDITIONS ON THE REVERSE SIDE OF THIS QUOTATION SHEET.

DATE PRINTED 02/14/12	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
--------------------------	---------------	----------	--------	---------------

REPLY DUE BY: 03/13/12 12:00 O'CLOCK NOON

NEEDED BY DATE	QUANTITY	UNIT	CAT. NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
	REQ LINE NUMBER : 0001					
	1	EA	AIRP	12R034401		
	AIRCRAFT RESCUE & FIRE FIGHTING VEHICLE (ARFF)					
	AS PER ATTACHED PROCUREMENT MANUAL					
	BIDDERS PLEASE CHECK/COMPLETE BELOW:					
	<input type="checkbox"/> FREIGHT IS INCLUDED IN THE QUOTED UNIT PRICE <input type="checkbox"/> WE WILL CHARGE FOR FREIGHT/DELIVERY IN THE AMT OF : \$					
	FOR ADDITIONAL INFORMATION CONTACT: MICHAEL BERNICH AT 314-551-5322					
	*** BID RESULTS MAY BE AVAILABLE 30 DAYS AFTER OPENING DATE. IF YOU DESIRE BID RESULTS, PLEASE INCLUDE A SELF ADDRESSED STAMPED ENVELOPE WITH YOUR BID. ***					
					<b>TOTAL</b> →	

NAME OF FIRM	STATE DELIVERY: CALENDAR DAYS	COMPTROLLER	Date
ADDRESS			
CITY	STATE	SIGNED BY:	SUPPLY COMMISSIONER
PHONE	Area Code ( )		Date



# **Lambert-St. Louis International Airport**

## **Aircraft Rescue & Fire Fighting (ARFF) Vehicle**

### **Procurement Manual**

BID # 42012Q0344

February 15, 2012

## TABLE OF CONTENTS

DESCRIPTION OF PROCUREMENT	2
SPECIAL CONDITIONS – DEPARTMENT OF TRANSPORTATION FAA	
<u>FEDERAL PROCUREMENT REQUIREMENTS</u>	
• Buy American Guidance	3
• Buy America Certification	4
• Component Cost Calculation Table	5
• Civil Rights Act of 1964	6
• Airport & Airways Improvement	7
• Disadvantaged Business Enterprise	8
• Lobbying and Influencing Federal Employees	9
• Access to Records and Reports	10
• Energy Conservation	11
• Rights to Inventions	12
• Trade Restriction Clause	13
• Termination of Contract	14
• Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion	15
• Breach of Contract Terms	16
• Clean Air and Water Pollution Control	17
• St. Louis Airport Authority DBE	18
INSTRUCTION TO BIDDERS	19
MANUFACTURER'S LIST	20
BID PROTEST PROCEDURES	21-23
<i>There are no pages 24 through 98</i>	
VEHICLE PROCUREMENT SPECIFICATIONS, CLASS 4	
AIRCRAFT RESCUE & FIRE FIGHTING VEHICLE	99-128

## REQUEST FOR BID PROPOSAL FOR AIRCRAFT RESCUE & FIRE FIGHTING (ARFF) VEHICLE

The City of St. Louis is soliciting sealed bids from qualified firms to furnish an Aircraft Rescue and Fire Fighting (ARFF) vehicle for Lambert St. Louis International Airport.

The scope of work shall include, but not necessarily be limited to:

**SCOPE.** A commercially produced diesel engine driven ARFF vehicle for an Index D airport. It should include a 1500 gallon water/Aqueous Film Forming Foam (AFFF) for suppression system: 450 lb potassium-based dry chemical and 460 lb halogenated agent complementary systems.

**CLASSIFICATION.** The ARFF vehicle shall be as classified in accordance with PART 139, Certification and Operations: Land Airports Serving Certain Air Carriers, Section 315, Aircraft Rescue and Firefighting: Index Determination; Section 317, Aircraft Rescue and Firefighting: Equipment and Agents; and Federal Aviation Administration (FAA) Advisory Circular (AC) 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles, as follows:

Airport Index	Vehicle Class	Minimum Rated Capacities (gallons/liters)
Index D	4	1500 gallon (5678 liter) water/AFFF solution

**VEHICLE CONFORMANCE/PERFORMANCE CHARACTERISTICS.** The ARFF vehicle will be in accordance with the applicable requirements of National Fire Protection Association (NFPA) 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition), and AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles.

**Technical proposal.** The offeror/contractor will provide an itemized technical proposal that describes how the proposed model complies with each characteristic of the Procurement Specification; a paragraph response to the characteristics section of this procurement specification shall be provided. The offeror/contractor will provide two copies of their commercial descriptive catalogs with their offer as supporting reference to the itemized technical proposal. The offeror/contractor will identify all modifications made to their commercial model in order to comply with the requirements herein. The vehicle furnished will comply with the "commercial item" definition of FAR 2.101 as of the date of award. Offerer must identify any deviations from the specifications. The purchaser reserves the right to require the offeror/contractor to prove that their product complies with the referenced commerciality requirements and each conformance/performance characteristics of this procurement specification.

**BUY AMERICAN PREFERENCES:** (Title 49 U.S.C. Chapter 501)

The successful bidder must comply with Title 49 U.S.C. Section 50101. Unless otherwise formally approved by the Federal Aviation Administration (FAA), all acquired steel and manufactured products installed under the AIP assisted project must be produced in the United States. Section of 50101(b) permits conditional waivers of this preference. Specifically, the FAA will consider a waiver if the bidder can demonstrate:

- (1) Applying subsection 50101(a) is inconsistent with the public interest;
- (2) The steel and goods produced in the United States are not produced in a sufficient and reasonably available amount or are not of a satisfactory quality;
- (3) The cost of components and subcomponents produced in the United States is more than 60 percent of the cost of all components and final assembly occurs within the United States
- (4) The inclusion of domestic material will increase the cost of the overall project by more than 25 percent.

As a condition of bid responsiveness, Bidder must indicate on the Buy American certification whether it intends to meet Buy American requirements by only installing 100% United States made steel and manufactured products or if they intend to request a permissible waiver to Buy America preferences.

Waivers determinations addressed under exceptions (1) and (2) will generally be made as part of the bid solicitation. Bidder may not request a waiver under exceptions (1) or (2).

The successful bidder that desires a waiver under exception (3) shall make the request by selecting the appropriate certification statement and complying with the following conditions:

- For equipment and material the FAA has already issued a waiver to AIP Buy American preferences as indicated on the current FAA Buy American conformance list, bidder shall submit a listing of specific equipment and material it proposes to install on the project prior to the issuance of a Notice-to-Proceed.
- For equipment and material the FAA has not previously issued a waiver to Buy American preferences, the bidder identified with the apparent low bid agrees to prepare and submit to the owner a waiver request and component calculation information within 15 calendar days of the date of the notice of apparent award of contract.

The successful bidder that desires a waiver under exception (4) shall make the request by selecting the appropriate certification statement and complying with the following conditions:

- Provide detailed proposal costs using domestic product(s) and the overall project cost.
- Provide detailed alternate proposal costs of the non-domestic product(s) and the overall project cost.
- If the proposal with domestic product(s) is more than 25% of the proposal with non-domestic product(s), the bidder may request a waiver under exception (4).

Bidder is hereby advised that Owner approval of any requested waiver is contingent upon approval by the FAA.

**Buy America Certification  
(Title 49 U.S.C. Section 50101)**

<b>PROJECT NAME:</b>	Aircraft Rescue and Fire Fighting Vehicle
<b>AIRPORT NAME:</b>	Lambert St. Louis International Airport
<b>AIP NUMBER:</b>	3-29-0085-133

This solicitation and any resulting contract are subject to the Buy America requirements of 49 U.S.C. Section 50101. The bidder certifies it and all associated subcontractors will comply with the Buy American preferences established under Title 49 U.S.C. Section 50101 as follows:

**U.S.C. Section 50101 - Buying goods produced in the United States**

- (a) Preference. - The Secretary of Transportation may obligate an amount that may be appropriated to carry out section 106(k), 44502(a)(2), or 44509, subchapter I of chapter 471 (except section 47127), or chapter 481 (except sections 48102(e), 48106, 48107, and 48110) of this title for a project only if steel and manufactured goods used in the project are produced in the United States.
- (b) Waiver. - The Secretary may waive subsection (a) of this section if the Secretary finds that -
  - (1) Applying subsection (a) would be inconsistent with the public interest;
  - (2) The steel and goods produced in the United States are not produced in a sufficient and reasonably available amount or are not of a satisfactory quality;
  - (3) When procuring a facility or equipment under section 44502(a)(2) or 44509, subchapter I of chapter 471 (except section 47127), or chapter 481 (except sections 48102(e), 48106, 48107, and 48110) of this title -
    - A. The cost of components and subcomponents produced in the United States is more than 60 percent of the cost of all components of the facility or equipment; and
    - B. Final assembly of the facility or equipment has occurred in the United States; or
  - (4) Including domestic material will increase the cost of the overall project by more than 25 percent.
- (c) Labor Costs. - In this section, labor costs involved in final assembly are not included in calculating the cost of components.

\* \* \* \* \*

As a matter of bid responsiveness, the bidder or offeror must complete and submit this certification with their bid proposal. The bidder must sign and date the certification. The bidder/offeror must indicate how they propose to comply with the Buy America provision by selecting one of the following certification statements.

- The bidder hereby certifies that it will comply with Title 49 U.S.C Section 50101(a) by only installing steel and manufactured products produced in the United States of America. The bidder further agrees that if chosen as the apparent low bid, it will submit documentation to the owner that demonstrate all steel and manufactured products are 100% manufactured in the United States.
- The bidder hereby certifies that it cannot fully comply with the Buy America preferences of Title 49 U.S.C Section 50101(a); the bidder therefore requests a waiver per Title 49 U.S.C Section 50101(b). The bidder further agrees that upon notification from the Owner, the bidder identified with the apparent low bid agrees to prepare and submit a waiver request and component calculation information to the owner within \_\_\_\_\_ calendar days of the date of the notice of apparent low bid.

\_\_\_\_\_  
Bidder's Firm Name

\_\_\_\_\_  
Date

\_\_\_\_\_  
Signature



## **CIVIL RIGHTS ACT OF 1964, TITLE VI – CONTRACTOR CONTRACTUAL REQUIREMENTS**

During the performance of this contract, the contractor, for itself, its assignees and successors in interest (hereinafter referred to as the "contractor") agrees as follows:

**1.1 Compliance with Regulations.** The contractor shall comply with the Regulations relative to nondiscrimination in federally assisted programs of the Department of Transportation (hereinafter, "DOT") Title 49, Code of Federal Regulations, Part 21, as they may be amended from time to time (hereinafter referred to as the Regulations), which are herein incorporated by reference and made a part of this contract.

**1.2 Nondiscrimination.** The contractor, with regard to the work performed by it during the contract, shall not discriminate on the grounds of race, color, or national origin in the selection and retention of subcontractors, including procurements of materials and leases of equipment. The contractor shall not participate either directly or indirectly in the discrimination prohibited by section 21.5 of the Regulations, including employment practices when the contract covers a program set forth in Appendix B of the Regulations.

**1.3 Solicitations for Subcontracts, Including Procurements of Materials and Equipment.** In all solicitations either by competitive bidding or negotiation made by the contractor for work to be performed under a subcontract, including procurements of materials or leases of equipment, each potential subcontractor or supplier shall be notified by the contractor of the contractor's obligations under this contract and the Regulations relative to nondiscrimination on the grounds of race, color, or national origin.

**1.4 Information and Reports.** The contractor shall provide all information and reports required by the Regulations or directives issued pursuant thereto and shall permit access to its books, records, accounts, other sources of information, and its facilities as may be determined by the Sponsor or the Federal Aviation Administration (FAA) to be pertinent to ascertain compliance with such Regulations, orders, and instructions. Where any information required of a contractor is in the exclusive possession of another who fails or refuses to furnish this information, the contractor shall so certify to the sponsor or the FAA, as appropriate, and shall set forth what efforts it has made to obtain the information.

**1.5 Sanctions for Noncompliance.** In the event of the contractor's noncompliance with the nondiscrimination provisions of this contract, the sponsor shall impose such contract sanctions as it or the FAA may determine to be appropriate, including, but not limited to:

- a. Withholding of payments to the contractor under the contract until the contractor complies, and/or
- b. Cancellation, termination, or suspension of the contract, in whole or in part.

**1.6 Incorporation of Provisions.** The contractor shall include the provisions of paragraphs 1 through 5 in every subcontract, including procurements of materials and leases of equipment, unless exempt by the Regulations or directives issued pursuant thereto. The contractor shall take such action with respect to any subcontract or procurement as the sponsor or the FAA may direct as a means of enforcing such provisions including sanctions for noncompliance. Provided, however, that in the event a contractor becomes involved in, or is threatened with, litigation with a subcontractor or supplier as a result of such direction, the contractor may request the Sponsor to enter into such litigation to protect the interests of the sponsor and, in addition, the contractor may request the United States to enter into such litigation to protect the interests of the United States.

**AIRPORT AND AIRWAY IMPROVEMENT ACT OF 1982, SECTION 520 - GENERAL CIVIL RIGHTS PROVISIONS**

The contractor assures that it will comply with pertinent statutes, Executive orders and such rules as are promulgated to assure that no person shall, on the grounds of race, creed, color, national origin, sex, age, or handicap be excluded from participating in any activity conducted with or benefiting from Federal assistance. This provision obligates the tenant/concessionaire/lessee or its transferee for the period during which Federal assistance is extended to the airport a program, except where Federal assistance is to provide, or is in the form of personal property or real property or interest therein or structures or improvements thereon. In these cases the provision obligates the party or any transferee for the longer of the following periods: (a) the period during which the property is used by the airport sponsor or any transferee for a purpose for which Federal assistance is extended, or for another purpose involving the provision of similar services or benefits or (b) the period during which the airport sponsor or any transferee retains ownership or possession of the property. In the case of contractors, this provision binds the contractors from the bid solicitation period through the completion of the contract. This provision is in addition to that required of Title VI of the Civil Rights Act of 1964.

## DISADVANTAGED BUSINESS ENTERPRISES

**Contract Assurance (§26.13)** - The contractor or subcontractor shall not discriminate on the basis of race, color, national origin, or sex in the performance of this contract. The contractor shall carry out applicable requirements of 49 CFR Part 26 in the award and administration of DOT assisted contracts. Failure by the contractor to carry out these requirements is a material breach of this contract, which may result in the termination of this contract or such other remedy, as the recipient deems appropriate.

**Prompt Payment (§26.29)** - The prime contractor agrees to pay each subcontractor under this prime contract for satisfactory performance of its contract no later than *[specify number]* days from the receipt of each payment the prime contractor receives from *[Name of recipient]*. The prime contractor agrees further to return retainage payments to each subcontractor within *[specify the same number as above]* days after the subcontractor's work is satisfactorily completed. Any delay or postponement of payment from the above referenced time frame may occur only for good cause following written approval of the *[Name of Recipient]*. This clause applies to both DBE and non-DBE subcontractors.

## **LOBBYING AND INFLUENCING FEDERAL EMPLOYEES**

(1) No Federal appropriated funds shall be paid, by or on behalf of the contractor, to any person for influencing or attempting to influence an officer or employee of any agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with the making of any Federal grant and the amendment or modification of any Federal grant.

(2) If any funds other than Federal appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of any agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with any Federal grant, the contractor shall complete and submit Standard Form-LLL, "Disclosure of Lobby Activities," in accordance with its instructions.

## **ACCESS TO RECORDS AND REPORTS**

The Contractor shall maintain an acceptable cost accounting system. The Contractor agrees to provide the Sponsor, the Federal Aviation Administration and the Comptroller General of the United States or any of their duly authorized representatives access to any books, documents, papers, and records of the contractor which are directly pertinent to the specific contract for the purpose of making audit, examination, excerpts and transcriptions. The Contractor agrees to maintain all books, records and reports required under this contract for a period of not less than three years after final payment is made and all pending matters are closed.

## **ENERGY CONSERVATION REQUIREMENTS**

The contractor agrees to comply with mandatory standards and policies relating to energy efficiency that are contained in the state energy conservation plan issued in compliance with the Energy Policy and Conservation Act (Public Law 94-163)

## **RIGHTS TO INVENTIONS**

All rights to inventions and materials generated under this contract are subject to regulations issued by the FAA and the Sponsor of the Federal grant under which this contract is executed.

## **TRADE RESTRICTION CLAUSE**

The contractor or subcontractor, by submission of an offer and/or execution of a contract, certifies that it:

- a. is not owned or controlled by one or more citizens of a foreign country included in the list of countries that discriminate against U.S. firms published by the Office of the United States Trade Representative (USTR);
- b. has not knowingly entered into any contract or subcontract for this project with a person that is a citizen or national of a foreign country on said list, or is owned or controlled directly or indirectly by one or more citizens or nationals of a foreign country on said list;
- c. has not procured any product nor subcontracted for the supply of any product for use on the project that is produced in a foreign country on said list.

Unless the restrictions of this clause are waived by the Secretary of Transportation in accordance with 49 CFR 30.17, no contract shall be awarded to a contractor or subcontractor who is unable to certify to the above. If the contractor knowingly procures or subcontracts for the supply of any product or service of a foreign country on said list for use on the project, the Federal Aviation Administration may direct through the Sponsor cancellation of the contract at no cost to the Government.

Further, the contractor agrees that, if awarded a contract resulting from this solicitation, it will incorporate this provision for certification without modification in each contract and in all lower tier subcontracts. The contractor may rely on the certification of a prospective subcontractor unless it has knowledge that the certification is erroneous.

The contractor shall provide immediate written notice to the sponsor if the contractor learns that its certification or that of a subcontractor was erroneous when submitted or has become erroneous by reason of changed circumstances. The subcontractor agrees to provide written notice to the contractor if at any time it learns that its certification was erroneously by reason of changed circumstances.

This certification is a material representation of fact upon which reliance was placed when making the award. If it is later determined that the contractor or subcontractor knowingly rendered an erroneous certification, the Federal Aviation Administration may direct through the Sponsor cancellation of the contract or subcontract for default at no cost to the Government.

Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render, in good faith, the certification required by this provision. The knowledge and information of a contractor is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.

This certification concerns a matter within the jurisdiction of an agency of the United States of America and the making of a false, fictitious, or fraudulent certification may render the maker subject to prosecution under Title 18, United States Code, Section 1001.

## **TERMINATION OF CONTRACT**

a. The Sponsor may, by written notice, terminate this contract in whole or in part at any time, either for the Sponsor's convenience or because of failure to fulfill the contract obligations. Upon receipt of such notice services shall be immediately discontinued (unless the notice directs otherwise) and all materials as may have been accumulated in performing this contract, whether completed or in progress, delivered to the Sponsor.

b. If the termination is for the convenience of the Sponsor, an equitable adjustment in the contract price shall be made, but no amount shall be allowed for anticipated profit on unperformed services.

c. If the termination is due to failure to fulfill the contractor's obligations, the Sponsor may take over the work and prosecute the same to completion by contract or otherwise. In such case, the contractor shall be liable to the Sponsor for any additional cost occasioned to the Sponsor thereby.

d. If, after notice of termination for failure to fulfill contract obligations, it is determined that the contractor had not so failed, the termination shall be deemed to have been effected for the convenience of the Sponsor. In such event, adjustment in the contract price shall be made as provided in paragraph 2 of this clause.

e. The rights and remedies of the sponsor provided in this clause are in addition to any other rights and remedies provided by law or under this contract.

**CERTIFICATION REGARDING DEBARMENT, SUSPENSION, INELIGIBILITY AND VOLUNTARY EXCLUSION**

The bidder/offeror certifies, by submission of this proposal or acceptance of this contract, that neither it nor its principals is presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participation in this transaction by any Federal department or agency. It further agrees by submitting this proposal that it will include this clause without modification in all lower tier transactions, solicitations, proposals, contracts, and subcontracts. Where the bidder/offeror/contractor or any lower tier participant is unable to certify to this statement, it shall attach an explanation to this solicitation/proposal.

## **BREACH OF CONTRACT TERMS**

Any violation or breach of terms of this contract on the part of the contractor or their subcontractors may result in the suspension or termination of this contract or such other action that may be necessary to enforce the rights of the parties of this agreement. The duties and obligations imposed by the Contract Documents and the rights and remedies available thereunder shall be in addition to and not a limitation of any duties, obligations, rights and remedies otherwise imposed or available by law.

## **CLEAN AIR AND WATER POLLUTION CONTROL**

Contractors and subcontractors agree:

- a. That any facility to be used in the performance of the contract or subcontract or to benefit from the contract is not listed on the Environmental Protection Agency (EPA) List of Violating Facilities;
- b. To comply with all the requirements of Section 114 of the Clean Air Act, as amended, 42 U.S.C. 1857 et seq. and Section 308 of the Federal Water Pollution Control Act, as amended, 33 U.S.C. 1251 et seq. relating to inspection, monitoring, entry, reports, and information, as well as all other requirements specified in Section 114 and Section 308 of the Acts, respectively, and all other regulations and guidelines issued thereunder;
- c. That, as a condition for the award of this contract, the contractor or subcontractor will notify the awarding official of the receipt of any communication from the EPA indicating that a facility to be used for the performance of or benefit from the contract is under consideration to be listed on the EPA List of Violating Facilities;
- d. To include or cause to be included in any construction contract or subcontract which exceeds \$ 100,000 the aforementioned criteria and requirements.

## **St. Louis Airport Authority Disadvantaged Business Enterprise**

*It is the policy of the St. Louis Airport Authority to practice nondiscrimination based on race, color, sex or national origin in the award of performance of this contract. The St. Louis Airport Authority has an established Disadvantaged Business Enterprise (DBE) program compliant with 49 CFR Part 26, which is applicable for the award and administration of a DOT-assisted contracts. Although there is no specific participation goal for this procurement action, we encourage bidders to consider participation of small business entities, including those owned and controlled by certified socially and economically disadvantaged enterprises (DBEs), minority business enterprises and women business enterprises.*

## INSTRUCTIONS TO BIDDERS

**Please carefully review all information requested in this bid package. Failure to submit required samples, literature, unit pricing, extended pricing, and any other requested information may result in disqualification of your bid or any portion of your bid.**

- As per attached specifications. Note: Bidder must indicate on separate sheet where item does not conform to specifications.
- Bid to include manufacturer specifications and catalogue cut. No exceptions!
- Time of performance 200 calendar days after contract award.
- Liquidated Damages of \$50 per day will be assessed for every day beyond time of performance.
- Import required bid form(s) attached: Vendor must complete, sign and return the enclosed "Buy American" form with their bid
- Award of contract will be based upon the most responsive bidder that submits the lowest price.
  
- *Bids will be awarded based on official specifications provided by Supply Division only and any related addenda. All inquiries must be in writing (letter/e-mail/fax) to the following buyer:*  
*Sharon Coleman – coleman@stlouiscity.com*  
*Fax# 314-622-4141 Phone# 314-622-4596*
  
- Please type name of contact person for this bid  
Name: \_\_\_\_\_  
Fax: \_\_\_\_\_  
Email: \_\_\_\_\_
  
- If freight or delivery charge to be billed, it must be included in this quote or it will not be paid.  
( ) Freight is included in the quoted unit price.  
( ) We will charge freight/delivery in the amount of: \$ \_\_\_\_\_
- Website Information - To Download Supply Bids go to: <http://stlouis-mo.gov/supply/bids-notices.cfm>  
(click on Bid Notices)
- Two or more bids submitted for one item (item rejected).
- Signature missing on bid or **any** required form.
- Buy American Form not completed or returned (may be rejected).
- Altered or erased unit prices (must be initialed).
- Faxed bid, unless specifically requested (will be rejected).
- Failure to submit required Bond (for Contracts only) by the date indicated.

The reasons indicated above may disqualify your bid. If you have any questions, call the buyer indicated on the RFP.

This form must be returned with your bid. I certify that I have read and understand the information above.

\_\_\_\_\_  
Manual Signature

\_\_\_\_\_  
Date

**Possible Manufacturers:**

1. Oshkosh MFG  
Oshkosh Airport Products Customer Service, Technical & Parts  
2602 American Dr.  
Appleton, WI 54912  
800-222-6635
  
2. Rosenbauer MFG  
Minnesota Division  
P.O. Box 549  
Wyoming, MN 55092  
651-462-1000 phone  
651-462-1700 fax
  
3. Emergency -1 MFG  
E-ONE  
1601 S. W. 37<sup>th</sup> Avenue  
Ocala, FL 34474  
352-237-1122 phone  
352-237-1151 fax
  
4. KME-Kovatch Organization  
One Industrial Complex  
Nesquehoning, PA 18240 USA  
Toll Free: 800-235-3928  
Phone: 570-669-9461  
Fax: 570-669-5124
  
5. Pierce MFG  
2600 American Drive  
P.O. Box 2017  
Appleton, WI 54912  
920-832-3000
  
6. American LaFrance Charleston (SC)  
109 Newton Way  
Summerville, SC 29483-7430  
843-486-7400

CITY OF ST. LOUIS, MISSOURI SUPPLY DIVISION  
BID PROTEST PROCEDURES

The following procedures apply to any bidder, proposer or other respondent (a "Bidder") desiring to protest any advertisement for bids or other solicitation for goods, equipment and other services (each a "Solicitation") by the Supply Division City of St. Louis, Missouri.

PRIOR TO BID OPENING

Any Bidder or potential Bidder desiring to file a protest concerning alleged improprieties in a Solicitation (e.g., as a result of improper or incomplete specifications) must submit the protest in writing to City of St. Louis, Commissioner of Supply not less than two (2) business days prior to the deadline established for the receipt of bids (the "Bid Deadline"). The protest must be in writing, signed by or on behalf of the Bidder or potential Bidder making the protest, and must:

- (1) identify the Bidder or potential Bidder submitting the protest;
- (2) identify the bid by name and number;
- (3) clearly state the factual and legal grounds for the protest; and
- (4) include any supporting information necessary or appropriate for the Commissioner of Supply to make a determination whether the protest has merit.

The Commissioner of Supply shall review the protest and, if any modifications to the Solicitation (including any plans or specifications) are necessary, the City of St. Louis will issue one or more addenda setting forth any changes, which addenda will be sent to each Bidder or Potential Bidder that has been identified by the City of St. Louis Supply Division. The City of St. Louis Supply Division will further, if City of St. Louis Supply Division determines necessary or appropriate, extend the Bid Deadline for Bidders to incorporate the modification into their bids. If City of St. Louis Commissioner of Supply determines no modifications are required, City of St. Louis Supply Division will notify the protestor of the Commissioner of Supply's decision with a response to each substantive issue raised by the protestor. The decision of the Commissioner of Supply on this type of protest is final.

AFTER BID OPENING

Any Bidder desiring to file a protest concerning alleged improprieties in sealed bid opening procedures or a Bidders compliance with Solicitation requirements must be delivered to and actually received by City of St. Louis's Commissioner of Supply within ten (10) calendar days of the date the protestor first knew or should have known of the basis for the protest, but in any event prior to award of a contract under the solicitation by City of St. Louis Commissioner of Supply. The protest must be in writing, signed by or on behalf of the Bidder making the protest, and must:

- (1) identify the Bidder making the protest;
- (2) identify the bid by name and number;

- (3) clearly state the factual and legal grounds for the protest, and;
- (4) including any supporting information necessary or appropriate for the Commissioner of Supply to make a determination whether the protest has merit.

City of St. Louis Commissioner of Supply shall make a determination on the protest based on the information provided and other such investigation as the Commissioner of Supply deems appropriate. City of St. Louis Supply Division shall inform the protestor in writing of the Commissioner of Supply's determination with respect to each substantive issue identified in the written protest.

#### AFTER AWARD

Any Bidder may protest an award made by City of St. Louis Supply Division under any Solicitation on the basis of City of St. Louis making award to other than the lowest and best bidder (or, for federally assisted contracts, to the lowest responsible bidder), or that the award does not otherwise comply with the terms of the Solicitation, by filing a protest within three (3) business days after award. The protest must be submitted in writing to City of St. Louis Commissioner of Supply, signed by or on behalf of the Bidder making the protest, and must:

- (1) identify the Bidder making the protest;
- (2) identify the bid by name and number;
- (3) clearly state the factual and legal grounds for the protest, and;
- (4) include any supporting information necessary or appropriate for the Commissioner of Supply to make a determination whether the protest has merit.

City of St. Louis Commissioner of Supply shall make a determination on the protest based on the information provided and such other investigation as the Commissioner of Supply deems appropriate. Supply Division shall inform the protestor in writing of the Commissioner of Supply's determination with respect to each substantive issue identified in the written protest.

#### UNTIMELY PROTESTS

Any protest which is not submitted to City of St. Louis Commissioner of Supply in a timely manner or otherwise in accordance with the procedures will be deemed invalid. The decision of the Commissioner of Supply that a protest has not been timely filed is final and cannot be appealed.

#### APPEALS

Any protestor that is aggrieved by any decision of the Commissioner of Supply may appeal the Commissioner of Supply's decision to the Board of Standardization. Any appeal of a decision of the Commissioner of Supply must be made in writing delivered to the Commissioner of Supply within three (3) business days of receipt of the notice of the decision of the Commissioner of Supply. The notice of appeal shall

be in writing, signed by or on behalf of the Bidder or potential Bidder making the protest, and must:

- (1) clearly identify the decision being appealed, including identifying the bid by project name and number;
- (2) clearly state the factual and legal ground for the appeal, and;
- (3) include any supporting information necessary for the Board of Standardization to make a determination whether the appeal has merit.

The Board of Standardization may request the parties affected by the appeal to provide such additional information as necessary to make a decision on the appeal. Following a determination on the appeal by the Board of Standardization, the Supply Division will notify the party making the appeal of the determination of the Board of Standardization with respect to each substantive issue raised in the appeal.

Any appeal from an action of the Board of Standardization in connection with any protest shall be made by a court of competent jurisdiction in accordance with applicable Missouri law. A decision by the Board of Standardization to reject all bids may not be the subject of a protest and is not appealable.

NO AWARD DURING PENDENCY OF PROTEST

City of St. Louis Commissioner of Supply will not make any award under any Solicitation during the pendency of any protest.

### 3.4. VEHICLE PROCUREMENT SPECIFICATION, CLASS 4

#### PROCUREMENT SPECIFICATION

##### Class 4

#### AIRCRAFT RESCUE AND FIRE FIGHTING (ARFF) VEHICLE

1. **SCOPE.** This Procurement Specification (PS) covers a commercially produced diesel engine driven ARFF vehicle for an Index D airport. It includes a 1500 gallon water/Aqueous Film Forming Foam (AFFF) fire suppression system: 450 lb potassium-based dry chemical and 460 lb halogenated agent complementary systems.

The ARFF vehicle is intended to carry rescue and fire fighting equipment for the purpose of rescuing aircraft passengers, preventing aircraft fire loss, and combating fires in aircraft.

2. **CLASSIFICATION.** The ARFF vehicle(s) covered by this PS are classified in accordance with Part 139, Certification and Operations: Land Airports Serving Certain Air Carriers, Section 315, Aircraft Rescue and Firefighting: Index Determination; Section 317, Aircraft Rescue and Firefighting: Equipment and Agents; and Federal Aviation Administration (FAA) Advisory Circular (AC) 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles, as follows:

Airport Index	Vehicle Class	Minimum Rated Capacities (gallons/liters)
Index D	4	1500 gallon (5678 liter) water/AFFF solution

3. **VEHICLE CONFORMANCE/PERFORMANCE CHARACTERISTICS.** The ARFF vehicle will be in accordance with the applicable requirements of National Fire Protection Association (NFPA) 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition), and AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles.

#### 3.1 General Administration Requirements.

3.1.1 **Manuals:** Technical manuals will consist of operator, service, and parts manuals. All manuals are required to be provided in hardcopy and in digital format on CDs when requested.

3.1.1.1 **Technical manuals.** The overall format for the manuals will be commercial. Each technical manual will have a title page. Line art will be used to the maximum extent possible for illustrations and parts lists. One complete set of engine and transmission parts, service and operator's manuals will be packed with each vehicle.

- a. The contractor will provide digitized manuals in CD format when requested in addition to or in place of printed paper copies.
- b. The contractor will provide two complete sets of hardcopy manuals and / or CDs when requested.

3.1.1.1.1 Operator's manual. The operator's manual will include all information required for the safe and efficient operation of the vehicle, including fire extinguishing systems, equipment, and any special attachments or auxiliary support equipment. As a minimum, the operator's manual will include the following:

- a. The location and function of all controls and instruments will be illustrated and functionally described.
- b. Safety information that is consistent with the safety standards established by the Occupational Safety and Health Administration (OSHA) and NFPA.
- c. All operational and inspection checks and adjustments in preparation for placing the vehicle into service upon receipt from the manufacturer.
- d. Tie down procedures for transport on a low-boy trailer.
- e. Warranty information and the period of the warranty coverage for the complete vehicle and for any component warranty that exceeds the warranty of the complete vehicle. Addresses and telephone numbers will be provided for all warranty providers.
- f. General description and necessary step-by-step instructions for the operation of the vehicle and its fire extinguishing system(s) and auxiliary equipment.
- g. A description of the post-operational procedures (draining, flushing, re-servicing, et cetera).
- h. Daily maintenance inspection checklists that the operator is expected to perform, including basic troubleshooting procedures.
- i. Disabled vehicle towing procedures.
- j. Procedures and equipment required for changing a tire.
- k. Schedules (hours, miles, time periods) for required preventative maintenance and required periodic maintenance.
- l. Line art drawing of the vehicle, including panoramic views (front, rear, left, and right sides) showing basic dimensions and weights (total vehicle and individual axle weight for the unloaded and fully loaded vehicle). For the purposes of this AC, "unloaded" is defined as a lack of agent, occupants and compartment load, and "loaded" is defined as including agent, occupants and compartment load.

3.1.1.1.2 Service manual. The service manual will identify all special tools and test equipment required to perform servicing, inspection, and testing. The manual will cover troubleshooting and maintenance as well as minor and major repair procedures. The text will contain performance specifications, tolerances, and fluid capacities; current, voltage, and resistance data; test procedures; and illustrations and exploded views as may be required to

permit proper maintenance by qualified vehicle mechanics. The manual will contain an alphabetical subject index as well as a table of contents. The service manual will contain at least the following, where applicable:

- a. Fire fighting system schematic(s).
- b. Hydraulic schematic.
- c. Pneumatic schematic.
- d. Electrical schematic.
- e. Winterization schematic.
- f. Fuel schematic.
- g. Schedules for required preventative maintenance and required periodic maintenance.
- h. Lubrication locations, procedures, and intervals for parts of the vehicle and equipment that require lubrication.

3.1.1.1.3 Parts identification manual. The parts manual will include illustrations or exploded views (as needed) to identify properly all parts, assemblies, subassemblies, and special equipment. All components of assemblies shown in illustrations or exploded views will be identified by reference numbers that correspond to the reference numbers in the parts lists. All purchased parts will be cross-referenced with the original equipment manufacturer's (OEM) name and part number. The parts identification manual will provide the description and quantity of each item used for each vehicle. The size, thread dimensions, torque specifications, and special characteristics will be provided for all nonstandard nuts, bolts, screws, washers, grease fittings, and similar items. The manual will contain a numerical index. The parts manual will contain a list of all of the component vendor names, addresses, and telephone numbers referenced in the parts list.

### 3.1.2 Painting, plating, and corrosion control.

3.1.2.1 Finish. Exterior surfaces will be prepared, primed, and painted in accordance with all of the paint manufacturer's instructions and recommendations. Vehicles will be painted and marked in accordance with AC 150/5210-5, Painting, Marking, and Lighting of Vehicles Used on an Airport. The interior finish of all compartments will be based on the manufacturer's standard production practice. This may include painting, texturing, coating or machine swirling as determined by the manufacturer. All bright metal and anodized parts, such as mirrors, horns, light bezels, tread plates, and roll-up compartment doors, will not be painted. All other surfaces capable of being painted must be in the appropriate yellow-green color.

3.1.2.2 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, Dissimilar Metals, will not be in contact with each other. Metal plating or metal spraying of dissimilar base metals to provide electromotively compatible abutting surfaces is acceptable. The use of

dissimilar metals separated by suitable insulating material is permitted, except in systems where bridging of insulation materials by an electrically conductive fluid can occur.

3.1.2.3 Protection against deterioration. Materials that deteriorate when exposed to sunlight, weather, or operational conditions normally encountered during service will not be used or will have a means of protection against such deterioration that does not prevent compliance with performance requirements. Protective coatings that chip, crack, or scale with age or extremes of climatic conditions or when exposed to heat will not be used.

3.1.2.4 Reflective stripes. A minimum eight (8) inch horizontal band of high gloss white paint or white reflective tape (Retroreflective, ASTM-D 4956-09, *Standard Specification for Retroreflective Sheeting for Traffic Control*, TYPE III & above) must be applied around the vehicle's surface.

3.1.2.5 Lettering. The manufacturer will apply the airport's 'Name' and 'Insignia' (if available) in a contrasting color or by decal on both sides of the vehicle in long radius elliptical arches above and below the lettering center line. The size of the lettering will be a minimum of 2½-inches to a maximum of 6-inches. Reflective lettering is allowed if the material is the same as that which is used for the reflective stripe (as specified in AC 150/5210-5).

3.1.3 Vehicle identification plate. A permanently marked identification plate will be securely mounted at the driver's compartment. The identification plate will contain the following information:

- a. NOMENCLATURE
- b. MANUFACTURER'S MAKE AND MODEL
- c. MANUFACTURER'S SERIAL NUMBER
- d. VEHICLE CURB WEIGHT: kg (pounds)
- e. PAYLOAD, MAXIMUM: kg (pounds)
- f. GROSS VEHICLE WEIGHT (GVW): kg (pounds)
- g. FUEL CAPACITY AND TYPE: gals (gallons)
- h. DATE OF DELIVERY (month and year)
- i. WARRANTY (months and km (miles))
- j. CONTRACT NUMBER
- k. PAINT COLOR AND NUMBER

A second permanently marked information data plate will be securely mounted on the interior of the driver's compartment. The plate will contain the information required by NFPA 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition), Section 1.3.5 Vehicle

Information Data Plate. A single plate that combines or contains the information required for both plates is acceptable.

### 3.1.4 Environmental conditions.

3.1.4.1 Vehicle operation and storage temperature conditions will vary with geographical location. Thus, the locality temperature range can go from -40° to 110°F. Refer to NFPA 414 for vehicle winterization criteria.

3.1.4.2 Extreme temperature range. The vehicle will be capable of satisfactory storage and operation in temperatures ranging from -40° to 110°F. The vehicle will be equipped with a cab, chassis, and agent winterization system, permitting operation at -40°F. The winterization system will not detract from the performance of the vehicle or the firefighting system in ambient temperatures up to 110°F. The vehicle chassis winterization system will maintain the engine coolant, lubricants, fuel, and electrical systems operational at ambient temperatures of -40°F. The vehicle agent winterization system will provide sufficient insulation and heating capacity, by means of hot circulating liquids and/or forced air heat exchangers, to permit satisfactory operation of the vehicle and firefighting systems for a 2-hour period at ambient temperatures as low as -40° F with the vehicle fully operational and the engine running. At the end of this 2-hour period, the vehicle will be capable of successfully discharging its agents. All compartments not winterized will be marked as such on the interior of the compartment. The marking will state that the compartment is not winterized and cannot be used for the storage of items capable of freezing.

3.1.5 Reduction of potential foreign object damage. All loose metal parts, such as pins, will be securely attached to the vehicle with wire ropes or chains. Removable exterior access panels, if provided, will be attached with captive fasteners.

### 3.1.6 Vehicle Mobility.

3.1.6.1 Operating terrain. The vehicle will be capable of operating safely on paved roads, graded gravel roads, cross country terrain, and sandy soil environments. Cross country terrain consists of open fields, broken ground, and uneven terrain. An off-road, high-mobility suspension system resulting in no more than 0.5 G<sub>rms</sub> acceleration at the driver's seat of the vehicle when traversing an 8-inch (20 cm) diameter half round at 35 mph (56 kph) must be provided. The suspension design by which the manufacturer meets the suspension performance requirements is at the manufacturer's discretion.

3.1.6.2 Gradeability. The fully loaded vehicle will be able to ascend any paved slope up to and including 50-percent.

3.1.6.3 Side slope stability. The fully loaded vehicle will be stable on a 30° side slope when tested in accordance with NFPA 414.

3.1.6.4 Cornering stability. The fully loaded vehicle will be stable in accordance with NFPA 414 when tested in accordance with NFPA 414.

3.2 Weights and dimensions.

3.2.1 Overall dimensions. The maximum dimensions listed below are desirable to ensure vehicles can be accommodated in existing fire stations. Likewise, the overall dimensions should be held to a minimum that is consistent with the best operational performance of the vehicle and the design concepts needed to achieve this performance and to provide maximum maneuverability in accordance with NFPA 414.

Vehicle Capacity /Dimensions	1500 Gallon
Length (inches/cm)	433/1100
Width (inches/cm, excluding mirrors)	124/315
Height (inches/cm)	154/391

**NOTE:** For Airport Operator Validation: Consult AC 150/5210-15, Aircraft Rescue and Fire Fighting Station Building Design, Appendix A, to ensure vehicles measurements do not exceed existing airport fire station dimensions.

<b>VEHICLE MEASUREMENT VALIDATION</b>
Not applicable.
ADO/FAA Approval: ⇨ _____

3.2.2 Angles of approach and departure. The fully loaded vehicle will have angles of approach and departure of not less than 30°.

3.2.3 Field of vision. The vehicle will have a field of vision in accordance with NFPA 414.

3.2.3.1 Mirrors. Combination flat and convex outside rearview mirrors will be installed on each side of the cab. The flat mirrors will be of the motorized remote control type, providing not less than 60° horizontal rotational viewing range. The flat mirrors will also have electrically heated heads. Mirror remote and heating controls will be located on the instrument panel within reach of the seated driver. To provide the driver a clear view of the area ahead of the vehicle and to eliminate potential blind spots, a rectangular mirror will be installed on the lower corner of each side of the windshield, having a minimum area of 35 square inches.

The vehicle will have a back-up (rear-view) camera with a display monitor mounted above the driver in the cab. Cameras and monitors that are designed to replace the function of the side-view mirrors are not an approved option in this specification.

3.3 Chassis and vehicle components.

3.3.1 Engine. The vehicle will have a turbocharged diesel engine that is certified to comply with the Environmental Protection Agency (EPA) and state laws for off-highway emission requirements at the time of manufacture. The engine and transmission must operate efficiently and without detrimental effect to any drive train components when lubricated with standard, commercially available lubricants according to the recommendations of the engine and transmission manufacturers.

3.3.1.1 Acceleration. The fully loaded vehicle will accelerate from 0 to 50 miles per hour (mph) on a level paved road within: 25 seconds.

3.3.1.2 Maximum speed. The fully loaded vehicle will attain a minimum top speed of 70 mph on a level, paved road.

3.3.1.3 Pump and roll on a 40-percent grade. The fully loaded vehicle will be capable of pump and roll operations on a paved, dry, 40-percent grade in accordance with NFPA 414.

3.3.1.4 Altitude. Where justified, the vehicle, including the pumping system, will be designed for operation at 2,000 feet above sea level.

<b>JUSTIFICATION</b>
Not Applicable
ADO/FAA Approval: ⇨ _____

3.3.2 Engine cooling system. The engine cooling system will be in accordance with NFPA 414. A label will be installed near the engine coolant reservoir reading "Engine Coolant Fill."

3.3.3 Fuel system. The fuel system will be in accordance with NFPA 414.

3.3.3.1 Fuel priming pump. The vehicle will be equipped with an electric or pneumatic fuel pump in addition to the mechanical fuel pump. The electric/pneumatic pump will be used as a priming pump capable of re-priming the engines fuel system.

3.3.3.2 Fuel tank. The vehicle will have one or two fuel tanks with a minimum usable capacity in accordance with NFPA 414, as amended by NFPA 414. Each tank will have a fill opening of 3 inches minimum, readily accessible to personnel standing on the ground and designed to prevent fuel splash while refueling. Each tank will be located and mounted so as to provide maximum protection from damage, exhaust heat, and ground fires. If more than one tank is furnished, means will be provided to assure equalized fuel level in both tanks. An

overturn fuel valve will be provided for each tank to prevent spillage in the event of a rollover. Each fuel tank must be prominently labeled "Diesel Fuel Only".

3.3.4 Exhaust system. The exhaust system will be in accordance with NFPA 414. The exhaust system will be constructed of high grade rust resistant materials and protected from damage resulting from travel over rough terrain. The muffler(s) will be constructed of aluminized steel or stainless steel. Exhaust system outlet(s) will be directed upward or to the rear, away from personnel accessing equipment compartments and the engine air intake, and will not be directed toward the ground.

3.3.5 Transmission. A fully automatic transmission will be provided. The transmission will be in accordance with NFPA 414.

3.3.6 Driveline. The vehicle driveline will be in accordance with NFPA 414. If the driveline is equipped with a differential locking control, a warning/caution label will be placed in view of the driver indicating the proper differential locking/un-locking procedures. The operator's manual will also include a similar warning/caution. All moving parts requiring routine lubrication must have a means of providing for such lubrication. There must be no pressure lubrication fittings where their normal use would damage grease seals or other parts.

3.3.7 Axle capacity. Each axle will have a rated capacity, as established by the axle manufacturer, in accordance with NFPA 414.

3.3.8 Suspension. The suspension system will be in accordance with NFPA 414 and AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles.

3.3.9 Tires and wheels. Tires and wheels will be in accordance with NFPA 414. The vehicle will be equipped with single tires and wheels at all wheel positions. The vehicle will be equipped with tubeless steel belted radial tires with non-directional on/off-road type tread mounted on disc wheel assemblies. Tire and wheel assemblies will be identical at all positions. Tires and wheels will be certified by the manufacturer for not less than 25 miles of continuous operation at 60 mph at the normal operational inflation pressure. A spare tire and wheel assembly will be provided; however, the spare tire and wheel assembly are not required to be mounted on the vehicle. Tires will be new. Retreads, recaps, or re-grooved tires will not be permitted.

Tire bead locks, where justified, may be installed on all tires and rims.

<b>JUSTIFICATION</b>
Not Applicable
ADO/FAA Approval: ⇒ _____

3.3.10 Towing connections. The vehicle will be equipped with towing connections in accordance with NFPA 414. The vehicle will be designed for flat towing; the capability to lift and tow the vehicle is not required. The tow connections may intrude into the 30 degree approach angle.

3.3.11 Brake system. The vehicle will be equipped with a multi-channel all-wheel antilock brake system with at least one channel for each axle. The brakes will be automatic, self-adjusting and fully air-actuated. Brakes will be in accordance with CFR 49 CFR 393.40 through 393.42(b), 393.43, and 393.43 through 393.52. The braking system, complete with all necessary components will include:

- a. Air compressor having a capacity of not less than 16 standard cubic feet per minute (SCFM).
- b. Air storage reservoir(s), each tank equipped with drain (bleed) valves, and with safety and check valves between the compressor and the reservoir tank.
- c. Automatic moisture ejector on each air storage reservoir. Manual air tank drains are acceptable if they are labeled, are centrally located in one compartment and are accessible by an individual standing at the side of the vehicle.
- d. Automatic slack adjusters on cam brakes or internal self-adjusting brakes on wedge brakes on all axles.
- e. Spring set parking brakes.

All components of the braking system will be installed in such a manner as to provide adequate road clearance when traveling over uneven or rough terrain, including objects liable to strike and cause damage to the brake system components. No part of the braking system will extend below the bottom of wheel rims, to ensure, in case of a flat tire, that the weight of the vehicle will be supported by the rim and the flat tire and not be imposed on any component of the braking system. Slack adjusters and air chambers will be located above the bottom edge of the axle carrier.

3.3.11.1 Air dryer. A replaceable cartridge desiccant air dryer will be installed in the air brake system. The dryer will have the capability of removing not less than 95 percent of the moisture in the air being dried. The dryer will have a filter to screen out oil and solid contaminants. The dryer will have an automatic self-cleaning cycle and a thermostatically controlled heater to prevent icing of the purge valve.

3.3.11.2 Compressed air shoreline or vehicle-mounted auxiliary air compressor. A flush mounted, check valved, auto-eject compressed air shoreline connection will be provided to maintain brake system pressure while the vehicle is not running. The shoreline will be flush mounted (not to extend outside the body line), located on the exterior of the vehicle, either on the left side rear corner of the cab, or at the rear of the vehicle. In lieu of a compressed air shoreline connection, the vehicle may be equipped with a 110 volt shoreline connected vehicle-mounted auxiliary air compressor. In lieu of a compressed air shoreline connection, the vehicle may be equipped with an electrical shoreline connected vehicle mounted auxiliary air compressor.

3.3.12 Steering. The vehicle will be equipped with power steering. Rear-wheel steering technology is not an approved vehicle option.

3.3.12.1 Steering effort. The steering system performance will be in accordance with NFPA 414.

3.3.12.2 Turning diameter. The fully loaded vehicle will have a wall to wall turning diameter of less than three times the overall length of the vehicle in both directions in accordance with NFPA 414.

3.3.13 License plate bracket. A lighted license plate bracket will be provided at the left rear and left front of the vehicle. The location of the left front bracket will be placed so as not to interfere with the operation of fire fighting systems.

3.4 Cab. The vehicle will have a fully enclosed two door cab of materials which are corrosion resistant, such as aluminum, stainless steel, or glass reinforced polyester construction. Steps and handrails will be provided for all crew doors, and at least one grab handle will be provided for each crew member, located inside the cab for use while the vehicle is in motion. The lowermost step(s) will be no more than 22 inches above level ground when the vehicle is fully loaded. A tilt and telescoping steering column will be provided.

3.4.1 Windshield and windows. The windshield and windows will be of tinted safety glass. Each door window will be capable of being opened far enough to facilitate emergency occupant escape in the event of a vehicle accident. The vehicle windows will have an electric control system.

3.4.2 Cab interior sound level. The maximum cab interior sound level will be in accordance with NFPA 414.

3.4.3 Instruments and controls. All instruments and controls will be illuminated and designed to prevent or produce windshield glare. Gauges will be provided for oil pressure, coolant temperature, and automatic transmission temperature. In addition to the instruments and controls required by NFPA 414, the following will be provided within convenient reach of the seated driver:

- a. Master warning light control switch,
- b. Work light switch(es), and
- c. Compartment "Door Open" warning light and intermittent alarm that sounds when a compartment door is open and the parking brakes are released or the transmission is in any position other than neutral.

3.4.4 Windshield deluge system. The vehicle will be equipped with a powered windshield deluge system. The deluge system will be supplied from the agent water tank and will have an independent pumping system. The deluge system activation switch will be located within reach of the seated driver and turret operator.

3.4.5 Forward Looking Infrared (FLIR). A forward looking infrared (FLIR) camera and in-cab monitor, meeting the requirements of NFPA 414, will be provided. In addition, the FLIR monitor described in NFPA 414 will have a minimum dimension of 10 in (25 cm) (measured diagonally) and be located in a position where it is visible to both the seated driver and turret operator.

3.4.6 Climate control system. The offeror/contractor's standard heater/defroster and air conditioning system will be provided. The climate control system will induct at least 60 cubic feet per minute of fresh air into the cab. Cab mounted components will be protected from inadvertent damage by personnel.

3.4.7 Seats. The driver seat will be adjustable fore and aft and for height. The turret operator's seat, located to the right front of the driver's seat, will be a fixed (non-suspension) type. Each seat will be provided with a Type 3 seat belt assembly (i.e., 3-point retractable restraint) in accordance with CFR 49 CFR 571.209. Seat belts must be of sufficient length to accommodate crew members in full Personal Protective Equipment (PPE).

3.4.7.1. Seat Options. Two types of seat options are allowed in the vehicle. A standard seat contains a hard/fixed back. For these seats, a remote-mounted bracket designed to store a Self-Contained Breathing Apparatus (SCBA) will be provided. The remote-mounted bracket for the driver and turret operator (at a minimum) must be placed inside the cab. The brackets for seat positions #3 and #4 may be placed outside of the cab if necessary. An SCBA seat, on the other hand, contains an opening which can accommodate someone wearing an SCBA. The chart below represents the user's stated preference for the vehicle seating configuration.

Position	Standard	SCBA-Seat	N/A
Driver	X		
Turret		X	
# 3		X	
# 4			X

**JUSTIFICATION**

Our units are manned by a 3 man crew for any airfield response. In addition all of our units have a minimum crew seating of driver plus 2

ADO/FAA Approval: ⇒ \_\_\_\_\_

3.4.8 Windshield wipers and washer. The vehicle will be equipped with electrically powered windshield wipers. The wiper arms and blades will be of sufficient length to clear the windshield area described by SAE J198, Windshield Wiper Systems - Trucks. Individual wiper controls will include a minimum of two speed settings and an intermittent setting. The wiper blades will automatically return to a park position, out of the line of vision. The vehicle will be equipped with a powered windshield washer system, including an electric fluid pump, a minimum one gallon fluid container, washer nozzles mounted to the wiper arms (wet arms), and a momentary switch.

3.4.9 Warning signs. Signs that state "Occupants must be seated and wearing a seat belt when apparatus is in motion" will be provided in locations that are visible from each seated position in accordance with NFPA 414."

3.4.10 Lateral accelerometer and/or stability control system. The vehicle will be equipped with a lateral accelerometer and/or an electronic stability control system in accordance with NFPA 414.

3.4.11 Monitoring and Data Acquisition System (MADAS). The vehicle will be equipped with a MADAS as prescribed by NFPA 414.

3.5 Body, compartments, and equipment mounting.

3.5.1 Body. The vehicle will have a corrosion-resistant body.

3.5.2 Compartments. The vehicle body will have lighted compartments in accordance with NFPA 414 with a minimum of 10 cubic feet of enclosed storage space.

3.5.2.1 Compartment doors. Storage compartments will have clear anodized aluminum, counterbalanced, non-locking, roll-up or single hinged doors as determined by the manufacturer. Door latch handles on roll-up doors will be full-width bar type. Door straps will be provided to assist in closing the compartment doors when the rolled up or hinged door height exceeds six feet above the ground.

3.5.2.2 Scuffplates. Replaceable scuffplates will be provided at each compartment threshold to prevent body damage from sliding equipment in and out of the compartments. The scuffplates will be securely attached to the compartment threshold but will be easily replaceable in the event of damage.

3.5.2.3 Drip rails. Drip rails will be provided over each compartment door.

3.5.2.4 Shelves. An adjustable and removable compartment shelf will be provided for every 18 inches of each vertical storage compartment door opening. Shelving adjustments will require no more than common hand tools, and will not require disassembly of fasteners. Shelves will support a minimum of 200 pounds without permanent deformation. Each shelf will be accessible to crew members standing on the ground or using a pull out and tip-down configuration. Each shelf will have drain holes located so as to allow for drainage of any water from the stowed equipment.

3.5.2.5 Drainage mats. Each compartment floor and shelf will be covered with a removable black mat designed to allow for drainage of any water from the stowed equipment.

3.5.3 SCBA storage tubes. A single compartment or tubes for storage of four SCBA bottles will be provided. If tubes are provided, two will be installed on each side of the vehicle. The tubes will be of sufficient size to accommodate the procuring agencies SCBA cylinders.

3.5.4 Ladder, handrails, and walkways. Ladder, stepping, standing, and walking surfaces will be in accordance with NFPA 414. Handrails will be provided in accordance with NFPA 414. The lowermost step(s) or ladder rungs will be no more than 22 inches (56 cm) above level ground when the vehicle is fully loaded. The lowermost steps may extend below the angle of approach or departure or ground clearance limits if they are designed to swing clear. The tread of the bottom steps must be at least 8 inches (20 cm) in width and succeeding steps at least 16 inches (40 cm) in width. The full width of all steps must have at least 6 inches (15 cm) of unobstructed toe room or depth when measured from, and perpendicular to, the front edge of the weight-bearing surface of the step.

3.5.5 Ancillary equipment. Ancillary equipment listed in NFPA 414 A.4.2.1 (1)-(17) is not covered by this Procurement Specification in accordance with AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles. Ancillary equipment is funded separately by other sources.

**NOTE:** Equipment funding will be obtained as a separate contract under the provisions of AC 150/5210-14, Aircraft Rescue and Fire Fighting Equipment, Tools, and Clothing.

3.6 Agent system.

3.6.1 Agent (fire) pump. The vehicle will be equipped with a centrifugal pump capable of providing the performance specified herein as prescribed by NFPA 414.

3.6.1.1 Agent system piping. All piping, couplings, and valves and associated components that come into contact with the agent will be in accordance with NFPA 414.

3.6.1.2 Tank to pump connection. A check valve and shutoff valve will be provided in each tank to pump line.

3.6.1.3 Piping, couplings, and valves. All agent system piping will conform to NFPA 414 criteria.

3.6.1.4 Overheat protection. The agent system will be equipped with an overheat protection system in accordance with NFPA 414. Overheat protection is not required on vehicles utilizing a pre-mixed pressurized foam system.

3.6.1.5 Pressure relief valves. The agent system will be equipped with pressure relief valves in accordance with NFPA 414.

3.6.1.6 Drains. The agent system will be equipped with a drainage system in accordance with NFPA 414.

3.6.2 Water tank. The vehicle will have a water tank with a manufacturer certified minimum capacity of at least 1500 gallons.

3.6.2.1 Water tank construction. The water tank will be constructed of passivated stainless steel, polypropylene, or Glass Reinforced Polyester (GRP) construction. All materials used will be capable of storing water, foam concentrate, and water/AFFF solutions.

3.6.2.2 Water tank overhead fill cover and drain. The water tank will be equipped with a 20 inch fill tower. The tower will be designed to allow for video inspection of the water tank interior. The water tank will incorporate a drainage system in accordance with NFPA 414.

3.6.2.3 Water tank overflow system and venting. The water tank will incorporate a venting system to relieve pressure on the tank during fill and discharge operations at maximum flow rates. It will have an overflow system to relieve excess fluid in the event of tank overflow. Drainage from the vent and overflow system will not flow over body panels or other vehicle components and will not be in the track of any of the tires. Tank vent hoses will be of the non-collapsible type.

3.6.2.4 Water tank top fill opening. A top fill opening of not less than 8 inches internal diameter with a readily removable ¼-inch mesh strainer will be provided. The fill opening may be incorporated as part of the manhole cover, and will be sized to accommodate a 2½-inch fill hose.

3.6.2.5 Water tank fill connections. The water tank will incorporate National Hose thread connections and will be in accordance with NFPA 414. If the vehicle is fitted with the "structural fire fighting capability option," the additional requirements listed in paragraph 3.6.8 must be incorporated.

3.6.3 Foam system. (NOTE: *The requirements of section 3.6.3 do not apply to pre-mixed pressurized foam systems.*)

3.6.3.1 Foam concentrate tank. The foam concentrate tank(s) will have a manufacturer certified working capacity sufficient for two tanks of water at the maximum tolerance specified in NFPA 412, Standard for Evaluating Aircraft Rescue and Fire-Fighting Foam Equipment for 3 to 6 percent foam concentrate (i.e., 7.0-percent).

3.6.3.1.1 Foam tank construction. The foam tank will be constructed of passivated stainless steel, polypropylene, or GRP construction. All materials used will be capable of storing foam concentrate.

3.6.3.1.2 Foam tank drain. The foam tank will incorporate a drain and drain valve. The valve will be on the left side of the vehicle and controlled by a crew member standing on the ground. The drain line will have a minimum 1½-inch I.D. The foam tank drain outlet will be located so that the contents of the tank can be drained into 5-gallon cans and 55-gallon drums.

3.6.3.1.3 Foam tank top fill trough. The foam tank will incorporate a top fill trough mounted in the top of the tank readily accessible to at least two crew members on top of the vehicle. The top fill trough will incorporate a cover, latch, and sealed so as to prevent spillage under any operating condition. The top fill trough will be designed to allow two standard 5-gallon foam concentrate containers to be emptied simultaneously. The top fill trough neck will extend sufficiently close to the bottom of the tank to reduce foaming to a minimum during the fill operation. The top fill trough will incorporate readily removable, rigidly constructed 10 mesh stainless steel, brass or polyethylene strainers. All components in and around the top fill trough will be constructed of materials that resist all forms of deterioration that could be caused by the foam concentrate or water.

3.6.3.2 Foam tank fill connections. The foam tank will incorporate a 1.5-inch National Hose thread female hose connection on both sides of the vehicle to permit filling by an external transfer hose at flow rates up to 25-gpm. The connections will be provided with chained-on long handled plugs or rocker lug plugs. The top of the connections will be no higher than 48 inches above the ground and readily accessible. The fill lines will incorporate check valves and readily removable, rigidly constructed ¼-inch mesh strainers. All components in the foam tank fill system will be constructed of materials that resist all forms of deterioration that could be caused by the foam concentrate or water.

3.6.3.2.1 Foam tank vent and overflow system. The foam tank will incorporate a vent system to relieve pressure on the tank during fill and discharge operations at maximum flow rates and an overflow system to relieve excess liquid in the event of tank overflow. Drainage from the vent and overflow system will not flow over body panels or other vehicle components and will not be in front of or behind any of the tires. Tank vent hoses will be of the non-collapsible type.

3.6.3.3 Foam transfer pump. A foam transfer pump will be provided and mounted in a compartment on the vehicle. The pump will be capable of transferring and drawing foam liquid concentrate at adjustable flow rates up to 25-gpm directly through the pump and loading

connections (see 3.6.3.2). All materials and components that come in contact with the foam will be compatible with the foam concentrate. The pump and its plumbing will have provisions for flushing with water from the water tank. A suitable length of hose with appropriate connections will be provided for filling the foam tank from an external foam storage container.

3.6.3.4 Foam flushing system. The foam concentrate system will be designed in accordance with NFPA 414 so that the system can be readily flushed with clear water.

3.6.3.5 Foam concentrate piping. All metallic surfaces of the piping and associated components that come into contact with the foam concentrate will be of brass, bronze, or passivated stainless steel. The foam concentrate piping will be in accordance with NFPA 414.

3.6.4 Foam proportioning system. The vehicle will have a foam proportioning system for Aqueous Film-Forming Foam (AFFF) (whether 3- or 6-percent foam concentrate) in accordance with NFPA 414. If a fixed orifice plate system is used, a plate will be provided for each percentage foam concentrate; the additional plate will be securely mounted in a protected location on the vehicle. A fire vehicle mechanic will be able to interchange the plates using common hand tools.

3.6.5 Primary vehicle turret. The vehicle will be equipped with a standard roof-mounted turret, high reach extendable turret, and/or high flow bumper mounted turret to serve as the primary source of agent delivery, as specified below:

3.6.5.1 Roof turret. The roof turret will be mounted near the front of the roof of the vehicle. It will have a non-air-aspirating, constant flow, variable stream nozzle with dual flow rates for foam or water rated as specified in NFPA 414. The discharge pattern will be infinitely variable from straight stream to fully dispersed. The roof turret will be power operated; power controls will be positioned for use by the driver and the crew member seated to the right of the driver. The type of nozzle or turret drain will be per the manufacturer's recommendation.

3.6.6 Bumper turret. The vehicle will be equipped with a joystick controlled, constant flow, non-air-aspirating, variable stream type:

low angle high volume dual rate (minimum 375/750 GPM) bumper turret.

The bumper turret will be capable of discharging at a minimum flow rates of foam or water as specified by the user, with a pattern infinitely variable from straight stream to fully dispersed. The bumper turret will be capable of automatic oscillation, with the range of oscillation adjustable up to 90° each side of center (left and right) with vertical travel capabilities of +45°/-20° meeting section 4.20.2 in NFPA 414.

3.6.7 Preconnected handline(s). Two 200 foot, 1¾-inch pre-connected woven jacket handline(s), with a 1½-inch control valve and a pistol grip nozzle, will be located on (or accessible from) each side of the vehicle. A safety system will be provided to prevent charging of the hose until the hose has been fully deployed. The handline(s) and nozzle(s) will be in accordance with NFPA 414, and will allow for a minimum of 95 gpm at 100 psi nozzle pressure. A control for charging each handline will be provided for operation by both the driver and the turret operator.

3.6.7.1 In addition, the vehicle will be equipped with the following handline: 100 feet of twinned 1-inch dry chemical / foam-water hose on a reel.

3.6.8. Structural fire fighting capability. The vehicle will be equipped with an agent system structural control panel, on the left side of the vehicle, operable while standing on the ground. Structural panel activation will be interlocked to operate only with the vehicle parking brakes set and the transmission in neutral position. Controls and instruments will be grouped by function. The control panel will be hinged or accessible from the rear for maintenance. Instruments will be lighted for night operation.

3.6.8.1 The structural panel will include, as a minimum, the following:

- a. Panel activation switch, including the panel lights.
- b. Engine tachometer.
- c. Engine oil pressure gauge with low pressure warning light.
- d. Engine coolant temperature gauge with high temperature warning light.
- e. A liquid filled gauge, or digital indicator for pump suction, -30 inches Hg vacuum to 600 psi.
- f. A liquid filled gauge, or digital indicator for pump pressure, 0 to 600 psi.
- g. An adjustable pump pressure using either an electronic pressure governor or manual control with a relief valve will be provided.
- h. Foam or water selection.
- i. Water and foam tank liquid level indicators, located adjacent to the water and foam tank fills.

3.6.8.2 The structural fire fighting capability will also require installation of the following items:

- a. A priming pump and control (for drafting using the large intake connection).
- b. Water tank isolation valve.
- c. Discharge connections. Two 2½-inch discharge connections with male National Hose threads will be provided. One 2½-inch discharge will be provided on each side of the vehicle. Each connection will be equipped with a cap, a quarter-turn control valve, a bleeder valve, and a pressure gauge. Each connection will be rated at 250-gpm minimum.
- d. Intake connections. The vehicle will be equipped with one valved 4½-inch intake connection on the left side. The vehicle will be equipped with one valved 2½-inch intake connection on the left side adjacent to the 4½-inch intake connection with both having either a 30° or 45° turn-down fitting. The 4½-inch intake connection will have male National Hose threads, a quarter-turn control valve, a bleeder valve, a strainer, and a cap. The 2½-inch intake connection will have rocker lug female National Hose threads, a quarter-turn control valve, a bleeder valve, a strainer, and a plug. The vehicle will be capable of filling its water tank by pumping from a draft, a hydrant, or a nurse truck through either of the intake connections without the use of a hose from a discharge connection to a tank fill connection.

3.6.9 Primary turret discharge nozzle. The vehicle will be equipped with a combination dry chemical/ AFFF nozzle of the entrainment type on the primary turret mounted on the cab roof.

3.7 Dry chemical agent system. The vehicle will be equipped with a 450 lb minimum capacity potassium bicarbonate dry chemical auxiliary agent system. The propellant gas cylinder will be replaceable within fifteen minutes by two crew members standing on the ground and be equipped with a cylinder replacement hoisting system. The propellant gas cylinder will be secured to withstand off-road operations. A pressure indicator will be visible to any person opening the tank fill cap. Blow-down piping will be directed beneath the vehicle. The dry chemical agent tank will include lifting rings and will have a nameplate indicating, as a minimum, the following:

- a. Extinguishing agent.
- b. Capacity.
- c. Weight full.
- d. Weight empty.
- e. Operating pressure.
- f. Hydrostatic test date.
- g. Type of agent required for re-servicing.

3.7.1 Dry chemical primary turret discharge nozzle. The vehicle will be equipped with a turret mounted on the cab roof with a combination dry chemical/AFFF turret of the concentric direct injection type, designed to entrain the dry chemical agent within the AFFF solution discharge. Dry chemical discharge control will be within reach of the driver and the turret operator.

3.7.2 Dry chemical hose reel. A hose reel, equipped with at least 100 feet of dry chemical hose, will be mounted in a compartment. Handline agent and purge controls will be mounted in or adjacent to the compartment. All electrical components will be sealed against entry of water. The hose reel will have both electric and manual rewind provisions. The manual rewind handle will be bracket mounted and stored in the compartment. A quick acting control will be provided to activate the handline from the cab of the vehicle.

### 3.8 Halogenated agent system.

3.8.1. A 460 lb. Halotron I clean agent system including an agent storage container, a hose reel and an argon propellant cylinder will be provided. The agent storage container will conform to ASME standards for unfixed pressure vessels. The system will be capable of discharging a minimum of 90% of the containerized agent without flow fluctuations or interruptions. The propellant gas cylinder will be replaceable within fifteen minutes by two crew members standing on the ground and be equipped with a cylinder replacement hoisting system. The propellant gas cylinder will be secured to withstand off-road operations. A pressure indicator will be visible to any person opening the tank fill cap. Blow-down piping will be directed beneath the vehicle. The Halotron I agent tank will include lifting rings and will have a nameplate indicating, as a minimum, the following:

- a. Extinguishing agent.
- b. Capacity.
- c. Weight full.
- d. Weight empty.
- e. Operating pressure.
- f. Hydrostatic test date.
- g. Type of agent required for re-servicing.

3.8.2. Halotron I hose reel. A Halotron I hose reel will be provided in a compartment on the side of the vehicle. The reel will include 150 ft. of 1 in. booster type hose and an appropriate nozzle. The hose reel will be equipped with an electric rewind motor with manual rewind provisions and rollers to facilitate hose deployment. A tension device will be installed to prevent the hose from inadvertently unreeling. The nozzle will be capable of discharging a minimum of 5 lb./ sec. of Halotron I agent in accordance with the performance requirements of the A/C. Controls at the reel will allow charging of the Halotron I agent in the agent storage container, and into the handline.

3.8.3. Halotron I system charging cylinder. One (1) 400 cu. ft. argon cylinder with an integral pressure gauge bottle will be provided for discharging the vehicle mounted Halotron I system. One (1) spare 400 cu. ft. argon cylinder will be provided. Each cylinder will have sufficient capacity to discharge all of the Halotron I agent in the agent storage container and perform a blow down operation of the system without requiring a cylinder change. A means of lifting the argon cylinder to its stored position or lowering it to ground level will be provided. The design will be such that it will allow one person to safely perform the argon cylinder re-servicing on the vehicle. The lifting/lowering mechanism will be stored on the vehicle adjacent to the nitrogen cylinder storage area. This storage provision must accommodate for the braking and for the high G forces experienced during off road travel as described in this specification.

3.9 Electrical systems and warning devices. The vehicle will have a 12-volt or 24-volt electrical and starting system in accordance with NFPA 414.

3.9.1 Alternator. An appropriate charging system, in accordance with NFPA 414, will be provided. The minimum continuous electrical load will include operation of the air conditioning system.

3.9.2 Batteries. Batteries will be of the maintenance-free type; addition of water will not be required during normal service life. The battery cover and vent system will be designed to prevent electrolyte loss during service and to keep the top of the battery free from electrolyte.

3.9.2.1 Battery compartment. The batteries will be enclosed in a weatherproof enclosure, cover, or compartment and be readily accessible.

3.9.3 Battery charger or conditioner. The vehicle will have a DC taper type battery charger or an automatic battery conditioner, or voltage monitoring system, providing a minimum 12 amp output. The charger/conditioner will be permanently mounted on the vehicle in a properly ventilated, accessible location. The charger/conditioner will be powered from the electrical shoreline receptacle (see 3.10.1). A charging indicator will be installed next to the receptacle. When a battery conditioner is provided, the conditioner will monitor the battery state of charge and, as necessary, automatically charge or maintain the batteries without gassing, depleting fluid level, overheating, or overcharging. A slave receptacle will be provided at the rear or on either side of the vehicle cab. Battery jump studs may be installed on the exterior of the battery box in lieu of a slave receptacle.

3.9.4 Electromagnetic interference. The vehicle electrical system will be in accordance with SAE J551-2 for electromagnetic interference.

3.9.5 Work lighting.

3.9.5.1 Cab interior lights. Cab interior light levels will be sufficient for reading maps or manuals. At least one red and one white cab interior dome light will be provided.

3.9.5.2 Compartment lights. White lighting sufficient to provide an average minimum illumination of 1.0 footcandle will be provided in each compartment greater than 4.0 cubic feet and having an opening greater than 144 square inches. Where a shelf is provided, this illumination will be provided both above and below the shelf. All compartments will be provided with weatherproof lights that are switched to automatically illuminate when compartment doors are opened and the vehicle master switch is in the 'on' position. Light switches will be of the magnetic (non-mechanical) type.

3.9.5.3 Ladder, step, walkway, and area lights. Non-glare white or amber lighting will be provided at ladders and access steps where personnel work or climb during night operations. In addition, ground lighting will be provided. Ground lights will be activated when the parking brake is set in accordance with AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles. These area lights will be controlled with three-way switches on the cab instrument panel and near the light sources. The switch located in the cab will be a

master switch and must be turned on before auxiliary switches near the light sources are operational.

3.9.5.4 Spot/Floodlights. Two spot/floodlights will be attached at the end of the primary turret or at the end of the HRET assembly. The lights will illuminate the area covered by the turret. Both lights will be controlled from switches in the cab. LED lights will be used.

3.9.5.5 Flood Lights. Two telescoping floodlights will be provided. One light will be mounted on the left and right sides of the vehicle. 250W LED lights will be used. Both lights will be mounted on extension tubes and controlled from switches in the cab and manually raised. To prevent these lights from accidental damage, the cab will be equipped with a visual warning signal to alert the driver if the lights are inadvertently left in the "up" position.

3.9.5.6 Scene Lights. A total of six high mounted floodlights will be provided to illuminate the work areas around the vehicle. Two lights will be mounted on the front and two will be mounted on each side of the vehicle. The lights will be powered by the vehicle alternator driven system or auxiliary generator, and the lights in the front will be controlled from switches in the cab. LED lights will be used.

### 3.9.6 Audible warning devices.

3.9.6.1 Siren. The vehicle will be equipped with an electronic siren system. The amplifier unit will include volume control and selection of "Radio," "PA," "Manual," "Yelp," "Wail," and "Hi-Lo" (European) modes, and a magnetic noise canceling microphone. The amplifier, microphone, and controls will be within reach of the driver and the turret operator. Siren activating foot switches will be located in front of the driver and the turret operator. The siren speaker will be rated at 100 watts minimum and will be located in a guarded position as low and as far forward on the vehicle as practical.

3.9.6.2 Horn. Dual forward facing air horns will be installed in protected locations near the front of the vehicle. Air horn activating foot switches will be located in front of the driver and the turret operator.

3.9.7 Emergency warning lights. All emergency warning lights must meet the requirements of AC 150/5210-5. Where applicable, LED lights will be used as the primary light type. Lighting units will be installed on the top front, sides, and rear of the vehicle to provide 360° visibility. A switch will be provided on the instrument panel to control all of the top, side, front and rear emergency warning lights. A switch will also be provided on the instrument panel to disable all lower emergency warning lights when desired. All lighting systems will meet NFPA 414 emergency lighting criteria.

3.9.7.1 Emergency warning light color. All emergency warning lights will meet the requirements of AC 150/5210-5.

3.9.7.2 Headlight flashing system. A high beam, alternating/flashing, headlight system will be provided. The headlight flasher will be separately switched from the warning light panel. All emergency warning lights will meet the requirements of AC 150/5210-5.

3.9.8 Radio circuit. The vehicle will have three separate 30 amp circuits with breakers and connections provided in a space adjacent to the driver and turret operator for installation of radios and other communications equipment after the vehicle has been delivered. To facilitate the installation of the communications equipment the manufacturer will provide three antennas pre-installed on top of the cab. *Radios are an airport responsibility and not part of this specification.*

3.9.9 Power receptacles.

3.9.9.1 Primary power receptacles. The vehicle will have two duplex 15-amp 110-volt power receptacles, one installed adjacent to the cab door on each side of the vehicle. Each duplex receptacle will include one straight blade and one twist-lock connection. These outlets will be powered by the generator.

3.9.9.2 Auxiliary power receptacles. The vehicle will have 2-12-volt auxiliary power receptacles mounted adjacent to the driver and crew member positions, preferably in the instrument panel.

3.9.9.3 Cable reel. The vehicle will be equipped with an electrical cable reel, located within a compartment. The reel will be equipped with 200 feet of 20 amp, 600 volt, 90°C insulated electrical cable. The electrical cable will be equipped with a rubber ball stop to prevent cable pull through during rewinding operations. A four-way roller guide will be provided on the cable reel to prevent chafing of cable insulation. The cable reel will have an electric rewind motor with provisions for manual rewind in the event of motor failure; the manual rewind handle will be securely stored near the cable reel. A portable weatherproof duplex outlet box, with built-in circuit breakers and twist-lock receptacles, will be provided for on the cable end. The cable reel will be powered by the auxiliary generator.

3.9.10 Auxiliary generator. A minimum 10 kilowatt (kW) (continuous rating), 120/240-volt, 60 hertz, diesel, hydraulic, or split shaft Power Takeoff (PTO)-driven generator will be provided.

3.10 Line voltage electrical system.

3.10.1 Electrical shoreline connection. The battery charger/conditioner will be powered from a covered, polarized, insulated, labeled, recessed (flush mounted), male, 110 volt AC auto-eject receptacle. The connection will be located on the exterior of the vehicle at the rear or on either side of the cab. A weatherproof charge meter will be installed next to the receptacle. A 15 amp rated, 110-120 volt, AC straight blade (non twist-lock) connector will be provided.

3.11 Not Applicable.

3.12 Quality of Workmanship. The vehicle, including all parts and accessories, will be fabricated in a thoroughly workmanlike manner. Particular attention will be given to freedom from blemishes, burrs, defects, and sharp edges; accuracy of dimensions, radii of fillets, and marking of parts and assemblies; thoroughness of welding, brazing, soldering, riveting, and painting; alignment of parts; tightness of fasteners; et cetera. The vehicle will be thoroughly cleaned of all foreign matter.

#### 4. REGULATORY REQUIREMENTS.

4.1 Recoverable Materials. The contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with Title 48: Federal Acquisition Regulations System, Part 2823—Environment, Conservation, Occupational Safety, and Drug-free Workplace, Subpart 2823.4 Use of Recovered Material, 403 Policy and 404 Procedures.

4.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired:

- a. competitively within a reasonable timeframe;
- b. meet appropriate performance standards, or
- c. at a reasonable price.

The prime contractor is responsible for ensuring that all subcontractors comply with this requirement. Information on the GPP can be found at:

[http://www.dot.gov/ost/m60/DOT\\_policy\\_letters/apl8\\_04.pdf](http://www.dot.gov/ost/m60/DOT_policy_letters/apl8_04.pdf) or FAR 23.404(b):  
[http://www.acquisition.gov/far/current/html/Subpart%2023\\_4.html](http://www.acquisition.gov/far/current/html/Subpart%2023_4.html).

#### 5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

- a. Performance inspection (see 5.2).
- b. Conformance inspection (see 5.3).

5.2 Performance inspection. The vehicle will be subjected to the examinations and tests described in 5.6.3.1 through 5.6.3.5 (if applicable). The contractor will provide or arrange for all test equipment, personnel, schedule, and facilities.

5.3 Conformance inspection. The vehicle will be subjected to the examinations and tests described in 5.6.3.1 through 5.6.3.5 (if applicable). The contractor will provide or arrange for all test equipment, personnel, and facilities.

5.4 Product conformance. The products provided will meet the performance characteristics of this PS, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The purchaser reserves the right to require proof of such conformance.

5.5 Technical proposal. The offeror/contractor will provide an itemized technical proposal that describes how the proposed model complies with each characteristic of this PS; a paragraph by paragraph response to the characteristics section of this PS will be provided. The offeror/contractor will provide two copies of their commercial descriptive catalogs with their offer as supporting reference to the itemized technical proposal. The offeror/contractor will identify all modifications made to their commercial model in order to comply with the requirements herein. The vehicle furnished will comply with the "commercial item" definition of FAR 2.101 as of the date of award. The purchaser reserves the right to require the offeror/contractor to prove that their product complies with the referenced commerciality requirements and each conformance/performance characteristics of this PS.

5.6 Inspection requirements.

5.6.1 General inspection requirements. Apparatus used in conjunction with the inspections specified herein will be laboratory precision type, calibrated at proper intervals to ensure laboratory accuracy.

5.6.2 Test rejection criteria. Throughout all tests specified herein, the vehicle will be closely observed for the following conditions, which will be cause for rejection:

- a. Failure to conform to design or performance requirements specified herein or in the contractor's technical proposal.
- b. Any spillage or leakage of any liquid, including fuel, coolant, lubricant, or hydraulic fluid, under any condition, except as allowed herein.
- c. Structural failure of any component, including permanent deformation, or evidence of impending failure.
- d. Evidence of excessive wear.
- e. Interference between the vehicle components or between the vehicle, the ground, and all required obstacles, with the exception of normal contact by the tires.

- f. Misalignment of components.
- g. Evidence of undesirable roadability characteristics, including instability in handling during cornering, braking, and while traversing all required terrain.
- h. Conditions that present a safety hazard to personnel during operation, servicing, or maintenance.
- i. Overheating of the engine, transmission, or any other vehicle component.
- j. Evidence of corrosion.
- k. Failure of the fire fighting system and sub-systems.

### 5.6.3 Detailed inspection requirements.

5.6.3.1 Examination of product. All component manufacturers' certifications, as well as the prototype and production/operational vehicle testing outlined in Table 1, will be examined to verify compliance with the requirements herein. Attention will be given to materials, workmanship, dimensions, surface finishes, protective coatings and sealants and their application, welding, fastening, and markings. Proper operation of vehicle functions will be verified as defined by NFPA 414, Acceptance Criteria chapter. A copy of the vehicle manufacturer's certifications will be provided with each vehicle in accordance with NFPA 414. The airport may accept a manufacturer or third party certification for any/all prototype and production/operational vehicle testing performed prior to delivery which proves that the vehicle meets the performance parameters of NFPA 414.

**Table 1. Vehicle Test Data**

<i>NFPA 414 paragraph</i>	<i>Test</i>
<b>Production Vehicle Operational Tests (NFPA 414 - Section 6.4)</b>	
(6.4.1)	Vehicle Testing, Side Slope
(6.4.2)	Weight / Weight Distribution
(6.4.3)	Acceleration. <i>NOTE: With the modification that the instrumentation must be a GPS-based electronic data collection system.</i>
(6.4.4)	Top Speed
(6.4.5)	Brake Operational Test
(6.4.6)	Air System / Air Compressor Test
(6.4.7)	Agent Discharge Pumping Test
(6.4.8)	Dual Pumping System Test (As Applicable)
(6.4.9)	Pump and Maneuver Test
(6.4.10)	Hydrostatic Pressure Test
(6.4.11)	Foam Concentration Test
(6.4.12)	Primary Turret Flow Rate Test
(6.4.13)	Piercing/Penetration Nozzle Testing (As Applicable)
<b>Prototype Vehicle Tests (NFPA 414 – Section 6.3)</b>	
(6.3.1)	Rated Water and Foam Tank Capacity Test
(6.3.2)	Cornering Stability. <i>NOTE: With the modification that the evasive maneuver / double-lane change test must be conducted at 35 mph (56 kph).</i>

<i>NFPA 414 paragraph</i>	<i>Test</i>
(6.3.3)	Vehicle Dimensions
(6.3.4)	Driver Vision Measurement
(6.3.5)	Pump and Roll on a 40 Percent Grade
(6.3.6)	Electrical Charging System
(6.3.7)	Radio Suppression
(6.3.8)	Gradability Test
(6.3.9)	Body and Chassis Flexibility Test
(6.3.10)	Service/Emergency Brake Test
(6.3.11)	Service/Emergency Brake Grade Holding Test
(6.3.12)	Steering Control Test
(6.3.13)	Vehicle Clearance Circle Test
(6.3.14)	Agent Pump(s)/Tank Vent Discharge Test
(6.3.15)	Water Tank Fill and Overflow Test
(6.3.16)	Flushing System Test
(6.3.17)	Primary Turret Flow Rate Test
(6.3.18)	Primary Turret Pattern Test
(6.3.19)	Primary Turret Control Force Measurement
(6.3.20)	Primary Turret Articulation Test
(6.3.21)	Handline Nozzle Flow Rate Test
(6.3.22)	Handline Nozzle Pattern Test
(6.3.23)	Ground Sweep/Bumper Turret Flow Rate Test
(6.3.24)	Ground Sweep/Bumper Turret Pattern Control Test
(6.3.25)	Undertruck Nozzle Test
(6.3.26)	Foam Concentration/Foam Quality Test
(6.3.27)	Warning Siren Test
(6.3.28)	Propellant Gas
(6.3.29)	Pressure Regulation
(6.3.30)	AFFF Premix Piping and Valves
(6.3.31)	Pressurized Agent Purging and Venting
(6.3.32)	Complementary Agent Handline Flow Rate and Range
(6.3.33)	Dry Chemical Turret Flow Rate and Range
(6.3.34)	Cab Interior Noise Test

## 6. PACKAGING.

6.1 Preservation, packing, and marking will be as specified in the Procurement Specification, contract or delivery order.

6.2 The vehicle must be delivered with full operational quantities of lubricants, brake and hydraulic fluids, and cooling system fluid all of which must be suitable for use in the temperature range expected at the airport.

6.3 The vehicle must be delivered with one complete load of firefighting agents and propellants. One complete load is defined as all of the agents and propellants necessary for the

vehicle to be fully operational. One load would include, at a minimum: one fill of a foam tank; one fill of a dry chemical tank (if applicable); one fill of a halogenated tank (if applicable); one spare nitrogen cylinder for a dry chemical system (if applicable); and one spare argon cylinder for a halogenated system (if applicable). Agents and propellants for required testing or training are not included. For the initial training period, water should be used in place of other extinguishing agents. The manufacturer may pre-ship agents and propellants to a receiving airport to reduce overall procurement costs.

6.4. The vehicle manufacturer must provide initial adjustments to the vehicle for operational readiness and mount any ancillary appliances purchased through the vehicle manufacturer as part of the vehicle.

## 7. TRAINING.

7.1 Upon delivery of the vehicle to the airport, the manufacturer must, at no additional cost, provide the services of a qualified technician for five consecutive days (or up to 8 days for an high reach extendable turret) for training. This is considered sufficient time for the purchaser to adjust shift work schedules to get maximum employee attendance to training sessions at some point during the training period. During this time sufficient repetitive learning opportunities must be provided by the manufacturer to allow various shifts to complete the training requirements.

7.2 The technician must provide thorough instruction in the use, operation, maintenance and testing of the vehicle. This setup must include operator training for the primary operators, which will give them sufficient knowledge to train other personnel in the functional use of all fire fighting and vehicle operating systems. Prior to leaving the vehicle, the technician should review the maintenance instructions with the purchaser's personnel to acquaint them with maintenance procedures as well as how to obtain support service for the vehicle.

7.3 Training must include written operating instructions, electronic training aids (videos/power point), or other graphics that depict the step-by-step operation of the vehicle. Written instructions must include materials that can be used to train subsequent new operators.

## 8. REFERENCED DOCUMENTS.

### 8.1 Source of documents.

8.1.1 The CFR may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington DC 20402.

Title 14, Code of Federal Regulations (CFR), Part 139, Certification of Airports (14 CFR Part 139)

Section 139.315 Aircraft Rescue and Firefighting: Index Determination.

Section 139.317 Aircraft Rescue and Firefighting: Equipment and Agents.

Section 139.319 Aircraft Rescue and Firefighting: Operational Requirements.

Title 49; Code of Federal Regulations (CFR), Part 393: Parts and Accessories Necessary for Safe Operation: Subpart C—Brakes.

Title 49; Code of Federal Regulations (CFR), Part 571, Motor Carrier Vehicle Safety Standards, Part 209, Standard No. 209; Seat Belt Assemblies

8.1.2 SAE documents may be obtained from SAE, Inc., 400 Commonwealth Drive, Warrendale PA 15096.

8.1.3 National Fire Protection Association (NFPA): NFPA documents may be obtained from NFPA, Batterymarch Park, Quincy MA 02269-9101.

NFPA 412, Standard for Evaluating Aircraft Rescue and Fire-Fighting Foam Equipment (2009 Edition)

NFPA 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition)

NFPA 1901, Standard for Automotive Fire Apparatus (2009 Edition)

8.1.4 Federal Aviation Administration (FAA): FAA ACs may be obtained from the FAA website: [http://www.faa.gov/regulations\\_policies/advisory\\_circulars/](http://www.faa.gov/regulations_policies/advisory_circulars/)

AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles

AC 150/5210-5, Painting, Marking, and Lighting of Vehicles Used on an Airport

FAA Orders, Specifications, and Drawings may be obtained from: Federal Aviation Administration, ATO-W CM-NAS Documentation, Control Center, 800 Independence Avenue, SW, Washington, DC 20591. Telephone: (202) 548-5256, FAX: (202) 548-5501 and website: [http://www.faa.gov/about/office\\_org/headquarters\\_offices/ato/service\\_units/techops/atc\\_facilities/cm/cm\\_documentation/](http://www.faa.gov/about/office_org/headquarters_offices/ato/service_units/techops/atc_facilities/cm/cm_documentation/)



**Print Class 4 Specification**